

AYL-12BI				Split Air conditioner, Inverter						
FUNCTION				FUNCTION						
Cooling	YES			Average season	YES					
Heating	YES			Warmer season	YES					
Design load				Colder season	NO					
Seasonal efficiency										
Item	symbol	value	unit	Item	symbol	value	unit			
Cooling	Pdesignc	3,2	kW	Cooling	SEER	6,1	--			
Heating / Average	Pdesignh	3,2	kW	Heating / Average	SCOP/A	4,0	--			
Heating / Warmer	Pdesignh	3,4	kW	Heating / Warmer	SCOP/W	5,1	--			
Heating / Colder	Pdesignh	--	kW	Heating / Colder	SCOP/C	--	--			
Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj				Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj						
Item	symbol	value	unit	Item	symbol	value	unit			
Tj = 35 °C	Pdc	3,21	kW	Tj = 35 °C	EERd	3,36	--			
Tj = 30 °C	Pdc	2,37	kW	Tj = 30 °C	EERd	4,82	--			
Tj = 25 °C	Pdc	1,50	kW	Tj = 25 °C	EERd	7,49	--			
Tj = 20 °C	Pdc	1,02	kW	Tj = 20 °C	EERd	10,25	--			
Declared capacity for heating/Average season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance / Average season, at indoor temperature 20 °C and outdoor temperature Tj						
Item	symbol	value	unit	Item	symbol	value	unit			
Tj = -7 °C	Pdh	2,91	kW	Tj = -7 °C	COPd	2,61	--			
Tj = 2 °C	Pdh	1,72	kW	Tj = 2 °C	COPd	4,04	--			
Tj = 7 °C	Pdh	1,12	kW	Tj = 7 °C	COPd	5,09	--			
Tj = 12 °C	Pdh	1,30	kW	Tj = 12 °C	COPd	6,37	--			
Tj = bivalent temperature	Pdh	2,71	kW	Tj = bivalent temperature	COPd	2,45	--			
Tj = operating limit	Pdh	2,91	kW	Tj = operating limit	COPd	2,61	--			
Declared capacity for heating / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj						
Item	symbol	value	unit	Item	symbol	value	unit			
Tj = 2 °C	Pdh	3,46	kW	Tj = 2 °C	COPd	3,32	--			
Tj = 7 °C	Pdh	2,19	kW	Tj = 7 °C	COPd	4,75	--			
Tj = 12 °C	Pdh	1,30	kW	Tj = 12 °C	COPd	6,37	--			
Tj = bivalent temperature	Pdh	3,46	kW	Tj = bivalent temperature	COPd	3,32	--			
Tj = operating limit	Pdh	3,46	kW	Tj = operating limit	COPd	3,32	--			
Bivalent temperature				Operating limit temperature						
Item	symbol	value	unit	Item	symbol	value	unit			
Heating / Average	Tbiv	-7	°C	Heating / Average	Tol	-10	°C			
Heating / Warmer	Tbiv	2	°C	Heating / Warmer	Tol	2	°C			
Heating / Colder	Tbiv	--	°C	Heating / Colder	Tol	--	°C			
Electric power input in power modes other than 'active mode'				Annual electricity consumption						
Off mode	P _{OFF}	0,00041	kW	Cooling	Q _{CE}	184	kWh/a			
Standby mode	P _{SB}	0,00041	kW	Heating / Average	Q _{HE}	1120	kWh/a			
Thermostat-off mode	P _{TO}	0,00206	kW	Heating / Warmer	Q _{HE}	933	kWh/a			
Capacity control				Other items	symbol	value	unit			
Fixed	NO			Sound power level (indoor/outdoor)	L _{WA}	55 / 62	dB(A)			
Staged	NO			Global warming potential	GWP	675	kgCO ₂ eq.			
Variable	YES			Rated air flow (indoor/outdoor)	--	560/2200	m ³ / h			
Name and address of the manufacturer or its authorised representative.				Manufacturer: SINCLAIR Corp. Ltd., 1-4 Argyll St., London, UK Zástupce: SINCLAIR Global Group s.r.o., Purkyňova 45, Brno, CZ						
Contact details for obtaining more information				info@ayton-world.com / www.ayton-world.com						